# Vader 350 Pro

Don't let the size fool you. This lightweight spot is a great choice for small to mid-sized venues. The light beam can be focused from a razor sharp line to wide open.

| | |
|---|---|
| **POWER CONSUMPTION** | *500 W* |
| **TOTAL LUMINAIRE OUTPUT** | *13 000 Lm* |
| **BEAM ANGLE** | *3 - 46 deg* |
| **COLOR MIX** | *CMY + CTO* |
| **NUMBER OF GOBOS / WHEEL** | *14 + open / 7 + open* |
| **DIMENSIONS** | *L210 x W337 x H588 mm* |
| **WEIGHT** | *15 kg* |

Favolite

Product specifications are subject to change without prior notice.

www.showlight.fi

# Vader 350 Pro

This compact and powerful moving head features a CMY + CTO color mixing system and a battery-operated menu. This fixture is powered by a flicker free 7000K (CRI>70) 300W LED and the zoom range is an impressive 3°-46°. A great choice for small to mid-sized venues. Because of its affordable price and 25% lighter weight compared to other fixtures in its segment, the Vader 350 Pro can be purchased and rigged in large quantities and it won't break your bank.

Don't let the size fool you. This little thing really packs a serious punch!

Favolite

www.showlight.fi

Product specifications are subject to change without prior notice.

# Vader 350 Pro

| | |
|---|---|
| **WEIGHT** | *15 kg* |
| **DIMENSIONS** | *L210 x W337 x H588 mm* |
| **POWER CONSUMPTION** | *500 W* |
| **VOLTAGE** | *100 - 240 V* |
| **IP RATING** | *IP20* |
| **LIFE EXPECTANCY** | *40 000h (L70)* |
| **POWER** | *300 W LED* |
| **TOTAL LUMINAIRE OUTPUT** | *13 000 Lm* |
| **PWM FREQUENCY** | *1 200 / 13 672 Hz* |
| **COLOR TEMPERATURE** | *7 000 K* |
| **CRI** | *70+* |
| **DIMMER** | *Electronic* |
| **DIMMER RESOLUTION** | *8-bit, internal 16-bit* |
| **DIMMER CURVE** | *Linear* |
| **STROBE** | *0.3 - 20 Hz, Pulse, Burst, Random* |
| **LENS** | *Symmetric* |
| **BEAM ANGLE** | *3 - 46 deg* |
| **ZOOM** | *Motorized* |
| **FOCUS** | *Motorized* |

| | |
|---|---|
| **COLOR MIX** | *CMY + CTO* |
| **COLOR MIX RESOLUTION** | *8-bit* |
| **VARIABLE COLOR TEMPERATURE** | *CTO* |
| **CTO** | *Linear* |
| **COLOR WHEEL** | *1 + 11* |
| **MOVEMENT** | *Motorized 16-bit* |
| **PAN** | *540 deg* |
| **TILT** | *270 deg* |
| **DMX CHANNELS** | *25 Ch* |
| **PROTOCOL** | *XLR DMX 512* |
| **WIRELESS CONTROL** | *Optional W-DMX* |
| **RDM** | *Yes* |
| **CONTROL MODES** | *25 Ch* |
| **GOBO WHEEL 1** | *Fixed* |
| **GOBO WHEEL 2** | *Rotating HD Glass* |
| **NUMBER OF GOBOS / WHEEL** | *14 + open / 7 + open* |
| **GOBO 2 DIAMETER** | *23 mm* |
| **GOBO 2 IMAGE DIAMETER** | *21 mm* |
| **GOBO 2 THICKNESS** | *1,25 - 2,00 mm* |

Favolite

Product specifications are subject to change without prior notice.

# Vader 350 Pro

| | |
|---|---|
| **PRISM 1** | *Indexable Circular 5 - Facet* |
| **FROST** | *On / Off* |
| **IRIS** | *Linear* |
| **IP RATING** | *IP20* |
| **BODY** | *Aluminium and stainless steel* |
| **HOUSING** | *Flame retardant plastic* |
| **HOUSING COLOR** | *Black or White* |
| **COOLING** | *Fan* |
| **POWER IN** | *TRUE1 or PowerCON* |
| **POWER OUT** | *TRUE1 or PowerCON* |
| **DATA IN** | *XLR5 or XLR3* |
| **DATA OUT** | *XLR5 or XLR3* |

Favolite

www.showlight.fi

Product specifications are subject to change without prior notice.