



HL-40

A new high power version of the HL-10 moving head wash with Osram LEDs and improved CTC. This wash light is powerful enough light up outdoor venues during daytime. This fixture has 19*40W RGBW LEDs and a backlight feature to illuminate the lens.

POWER CONSUMPTION	<i>652 W</i>
LIGHT SOURCE	<i>19 pcs 40 W Osram Ostar Stage RGBW LED</i>
COLOR MIX	<i>RGBW</i>
BEAM ANGLE	<i>11 - 58 deg</i>
DIMENSIONS	<i>L324 x W202.5 x H390.5 mm</i>
WEIGHT	<i>8,2 kg</i>

Hi-LTTE

www.showlight.fi

HL-40



WEIGHT	8,2 kg
DIMENSIONS	L324 x W202.5 x H390.5 mm
POWER CONSUMPTION	652 W
VOLTAGE	100 - 240 V
IP RATING	IP20
LED	OSRAM OSTAR Stage®
LIFE EXPECTANCY	40 000 h (L70)
POWER	Main beam: 19 x 40 W RGBW, Background: 30 x 0.2 W RGB
DIMMER	Electronic
DIMMER RESOLUTION	8-Bit
DIMMER CURVE	Linear
STROBE	Electronic Strobe, Pulse, Random, Custom 0 - 5.10 sec strobe
LENS	Symmetric wash
BEAM ANGLE	11 - 58 deg
ZOOM	Motorized
COLOR MIX	RGBW
COLOR MIX RESOLUTION	8-Bit
CTC	Variable

MOTORIZED	16-bit
PAN	540 deg
TILT	212 deg
PROTOCOL	XLR DMX 512
RDM	Yes
CONTROL MODES	25 Ch
LENS ILLUMINATION	RGB
IP RATING	IP20
BODY	Metal
HOUSING	Flame retardant plastic
HOUSING COLOR	Black
COOLING	Fan
POWER IN	PowerCON
POWER OUT	PowerCON
DATA IN	XLR3 and XLR5
DATA OUT	XLR3 and XLR5

Hi-LTTE

www.showlight.fi