

HT-700



A versatile and sturdy multi environment profile with a reasonable price tag.

Thanks to it's robust aluminium housing, the HT-700 is a top choice for demanding outdoor applications.

POWER CONSUMPTION *900 W*

BEAM ANGLE *5.5 - 50 deg*

COLOR MIX *CMY + CTO*

FRAMING SYSTEM *4 blades +/- 45 deg*

DIMENSIONS *L326 x W473 x H705 mm*

WEIGHT *43 kg*

IP RATING *IP65*

Hi-LITE

www.showlight.fi

HT-700

WEIGHT 43 kg
DIMENSIONS L326 x W473 x H705 mm
POWER CONSUMPTION 900 W
VOLTAGE 100 - 240 V
IP RATING IP65

LIFE EXPECTANCY 20 000 h
POWER 700 W LED
COLOR TEMPERATURE 8 000 K
CRI 80+

DIMMER Electronic
DIMMER RESOLUTION 16-bit
DIMMER CURVE Linear, Square, S - curve
STROBE 0.3 - 25 Hz, Pulse, Random

LENS Symmetric
BEAM ANGLE 5.5 - 50 deg
ZOOM Motorized
FOCUS Motorized

COLOR MIX CMY + CTO
COLOR MIX RESOLUTION 8-bit
VARIABLE COLOR TEMPERATURE CTO
CTO Linear
COLOR WHEEL 1 + 6

MOVEMENT Motorized 16-bit
PAN 540 deg
TILT 270 deg

DMX CHANNELS 34 Ch
PROTOCOL XLR DMX 512
WIRELESS CONTROL DMX (Optional)
RDM Yes
CONTROL MODES 34 Ch

GOBO WHEEL 1 Fixed
GOBO WHEEL 2 Rotating HD Glass
NUMBER OF GOBOS / WHEEL 6 + 2 open / 6 + open

Hi-LITE

www.showlight.fi

HT-700

PRISM 1 *Rotating Indexable
Circular 3 - Facet*

IRIS *Linear*

**FRAMING
BLADES** *4*

**FRAMING
SYSTEM ROTATION** *+/- 45 deg*

IP RATING *IP65*

BODY *Aluminium*

HOUSING *Aluminium*

**HOUSING
COLOR** *Black*

COOLING *Fan*

POWER IN *TRUE1*

DATA IN *XLR5 or XLR3*

DATA OUT *XLR5 or XLR3*

Hi-LITE

www.showlight.fi