

# SaanaWASH2 Zoom



The next generation of our distinguished wash light. Updated with high CRI white LEDs and redesigned handles for convenient carrying.

**POWER CONSUMPTION**     *500 W*

**LED**     *RGBW (White CRI >90)*

**COLOR RENDERING INDEX (CRI)**     *Ra >94, R9 >91*

**BEAM ANGLE**     *7 - 58 deg*

**COLOR MIX**     *Main beam: RGBW,  
Background: RGB*

**SEGMENTS**     *4 horizontal,  
9 LEDs in a row*

**DIMENSIONS**     *L 124 x W 508.5 x H 323 mm*

**WEIGHT**     *15 kg*

**IP RATING**     *IP65*

*showlight*

[www.showlight.fi](http://www.showlight.fi)

# *SaanaWASH2 Zoom*



The second version of our versatile wash light. We added high CRI white LEDs for superb TV compatibility. Ergonomic handles have also been added to the fixture to make it easier to carry.

A wide zoom range of 7 - 58 degrees makes this the perfect fixture for lighting a variety of objects or shows.

This fixture has an IP rating of IP65, and has been extensively tested in the harsh Finnish winter, which makes it a great choice for outdoors even in bad weather.

*showlight*

[www.showlight.fi](http://www.showlight.fi)

# SaanaWASH2 Zoom



**WEIGHT** 15 kg  
**DIMENSIONS** L124 x W508.5 x H323 mm  
**POWER** 500 W  
**CONSUMPTION**  
**VOLTAGE** 230 V  
**IP RATING** IP65

**LED** RGBW (White CRI >90)  
**LIFE EXPECTANCY** 40 000h (L70)

**POWER** Main beam:  
36 x 15 W RGBW,  
Background:  
72 x 0.2 W RGB

**TOTAL LUMINAIRE OUTPUT** 8500 lx @ 5 m 7 deg

**COLOR TEMPERATURE** 2 000 K - 10 000 K

**PWM FREQUENCY** 3 000 Hz

**CRI** Ra >94 , R9 >91

**DIMMER** Electronic

**DIMMER RESOLUTION** 8-bit

**DIMMER CURVE** Linear, Exponential,  
Logarithmic, S-curve

**STROBE** 0 - 20 Hz, Random Pulse,  
Ramp Up, Ramp Down,  
Random Strobe

**LENS** Symmetric

**BEAM ANGLE** 7 - 58 deg

**ZOOM** Motorized

**COLOR MIX** Main beam: RGBW,  
Background: RGB

**COLOR MIX RESOLUTION** 8-bit

**MOVEMENT** Manual

**TILT** Tilt +/- 80 deg

**DMX CHANNELS** 37 Ch

**PROTOCOL** XLR DMX 512

**WIRELESS CONTROL** WDMX 2.4G

**RDM** Yes

**CONTROL MODES** 3, 4, 5, 15, 20,  
21, 37 Ch

**LENS ILLUMINATION** RGB

**SEGMENTS** 4 horizontal,  
9 LEDs in a row

*showlight*

[www.showlight.fi](http://www.showlight.fi)

# *SaanaWASH2 Zoom*

**BODY** *Aluminium, Steel*

**HOUSING** *Aluminium,  
Tempered glass*

**HOUSING  
COLOR** *Black*

**COOLING** *Temperature  
controlled fan*

**POWER IN** *TRUE1*

**POWER OUT** *TRUE1*

**DATA IN** *XLR3 and XLR5*

**DATA OUT** *XLR3 and XLR5*

*showlight*

[www.showlight.fi](http://www.showlight.fi)